



SC EDGE

Group riding has never been so exciting. The SC-EDGE is powered by Cardo's ground-breaking 2nd generation Dynamic Mesh intercom system. Enabling you to connect with up to 15 riders effortlessly, creating a flexible, self-healing network. Whether you're riding in formation or scattered over miles, DMC ensures clear, reliable communication, making group rides smoother and more enjoyable.

20



2ND GENERATION DMC Easy grouping. Auto healing. Best sounding intercom.



OVER-THE-AIR SOFTWARE UPDATES No cables needed, ever!



NATURAL VOICE OPERATION Just talk, your unit will do the rest.



FM RADIO Built-in FM Radio with 6 channel presets.



LIVE INTERCOM Wideband sound, self-healing connection.



RANGE Connect up to 15 riders and takes only 5 seconds to set up. Range of up to 1.6km/1 mi*.



SCHUBERTH

CROSS-BRAND CONNECTIVITY Seamlessly connects with any other major brand.

SPECIFICATIONS CONNECTIVITY BATTERY

GENERAL

Universal compatibility Operating temperature: -20°C to 55°C / -4°F to 131°F

FM Radio: Operating frequencies 76-108 MHz

RDS - Radio Data System

6 preset station memory

Software updates:

Over-The-Air updates

USB cable updates

Device settings:

Cardo Connect App

DIMENSIONS

Back unit: Height: 40mm | Length: 80mm Depth: 27mm | Weight: 45g Side Unit: Height: 28mm | Length: 76mm Depth: 14mm | Weight: 15g 2 channels for mobile phone and GPS Bluetooth® 5.2 TFT connectivity DMC INTERCOM 2nd gen Dynamic Mesh Communication Group size: up to 15 riders

Rider to rider range: up to 1.6km / 1mi* DMC group range: up to 8km / 5.0 mi

BLUETOOTH® INTERCOM

Universal Bluetooth® intercom Auto-reconnect, Live intercom

USER INTERFACE

Natural Voice Operation

Multilingual status announcements

AUDIO

Automatic volume control

Talk time: 13 hours Charging time: up to 2 hours Fast charge: 2 hours talk time after 20 min Standby time: 10 days

CERTIFICATES

CE FCC / IC SIG BT UKCA

CODE

P/N: SCHB0001

*If the SC EDGE communication system is installed on full carbon helmets, the maximum communication range is limited to 400 meters in open terrain without obstacles, due to the electromagnetic interference shielding properties of the carbon fiber.

